



15" Touchscreen Kit resistive 5-wire

Art.Nr.: 301.4515xx

Environmental Conditions

Size	15"
Glass Thickness	2mm
Operating Temperature	-20°C ~ 70°C
Operating Humidity	5% ~ 96%RH (no dew falls)
Storage Temperature	-25°C ~ 80°C
Storage Humidity	5% ~ 96% RH (no dew falls)
Water Spray	not damaged by running water applied to the active area

Vibration

Withstand 0.1 inches peak to peak excursion, at a frequency of 5 to 455 Hz, for a period of 15 minutes in each of three axes.

Chemical Resistance

The touch panel active area of the touchscreen is resistant to the following chemicals when exposed for a period of one hour at 21°C:

- Aceton
- Ammonia-based glass cleaners
- Common foods and beverages
- Hexane
- Isopropyl alcohol
- Methylene chloride
- Methyl ethyl ketone
- Mineral spirits
- Turpentine

Electrical Characteristics

Supply Voltage	+5VDC, nominal
Contact Bounce	less than 10ms (input by finger)
Lead to Lead Resistance	40Ω ~ 100Ω (between X-Y) 50Ω ~ 10Ω (between X-LX) 50Ω ~ 10Ω (between Y-LX) 40Ω ~ 100Ω (between LX-LY)
Contact Bounce	Less than 10ms (input by finger)
Electrostatic Discharge Protection	Withstands 20 discharges of 15kV, distributed randomly across the active area with proper transient protection. (per EN 61000-4-2,1995)

Options:

301.451150	USB Interface
301.451510	RS232 Interface

Mechanical Characteristics

Activation force	Less than 40gr. Using by the silicone finger, hardness = 60° of diameter 16mm
Input Methods	Finger, glove hand, pen or stylus
Surface Hardness	Meets pencil hardness 3H (per ASTM D3363)
Position Accuracy (Linearity)	Less than 1%
Resolution	Based on controller resolution of 4096 x 4096
Cable	Type: F.C.C. (flat conductor cable) 300mm Connecting area with touch panel The tensile force: vertical to touch panel 2.0kg straight to touch panel 1.0kg Connecting type: 5 points soldering adding UV glue Cable fold: 10 time in 1R, 180 degrees Detail specification: ETC test, No.: ET.88T-12-102-C00
Connector	Five-position, 0.025inch (0.632mm square post receptacle with 2.54mm centers The times of insertions and withdrawals: at least 100 times.

Reliability

	The following characteristics are generated by evaluating test samples after 2 hours leaving in the room condition when each of the reliability test finishes.
Storage Temperature-high	80°C for 240 hours (at ambient humidity)
Storage Temperature-low	-25°C for 240 hours
Thermal Shock	-20°C (1hr.) ~ 70°C (1hr.) 10 cycles
High Temp./Humidity Test	60°C/90%RH: 240hours
Operating Life 1:	250g, 1 activations / sec (By using Silicone finger)
Hitting Key Test	More than 35.00.000 time (By using Silicone finger)
Operating Life 2:	250g, 4.5mm / sec. (By using polyester finger)
Writing Test	More than 1.000.000 times (By using polyester finger)

Optical Performance

Light Transmission	75~85% (typical value) (per ASTM D1003)
--------------------	---

