



## Panel PC

# PP-104BEVI10



### Display & Touch

Panel	10.4" TFT LCD
Resolution	800x600
Chipset	855GME Built in Extreme Graphics 2VGA
Memory	shared system memory up to 64MB
Touchscreen	resistive Type IP 65/NEMA 4 water / dust proof aluminium front bezel

### System

CPU	VIA Eden 1GHz Low-power CPU
Chip	CIA CLE266 VT8623 + VT8235
BIOS	4MB AMI Flash BIOS
VGA	VIA CLE266 built-in AGP 4x graphics, shared system memory up to 64 MB
Audio	AC 97 audio with Line-out, Line-in, Mic-in with external RCA connectors
LAN	Supports 10/100 Base-T with external RJ-45 connection WOL/PXE function
Memory	One DDR SDRAM SO-DIMM socket, support up to 1GB memory
I/O	ICH4
IDE	44-pin (2.0mm pitch) Ultra DMA 33 IDE Interface x2
WDT	1~255 minutes, software programmable

### Storage

HDD	1x2.5" IDE HDD Internal drive bay Optional anti-vibration HDD kit
-----	--

### Expansion

PCMCIA	PCMCIA Type I/II/III 32-bit Card Bus slot x1
Mini PCI	1x 32bit Mini-PCI Socket
USB 2.0	4x USB 2.0 connectors
COM	DB9x3
LAN	Supports 10/100 Base-T with external RJ-45 connector WOL/PXE function
KB/Mouse	1x PS/2 Keyboard & Mouse
Audio	Line-in, Line-out, Mic-in

### Mechanical & Environmental

Power Input	AC 90~264V / 47~63 Hz (optional DC24V adaptor)
Operating Temperature	0~40°C (fanless)
Relative Humidity	10%~90%, non-condensing
Dimensions	302x215x43.5mm (38mm depth without front bezel)