HYUNDAI IT CO., LTD.

HYUNDAI IT CO., LTD.

OUTDOOR DIGITAL SIGNAGE

Full color LED display CLASS MODEL

| Outdoor | HO2.9 |
|---------|-------|
|---------|-------|


KEY FEATURES

- Screen Ratio Implementaion.
- IP65 Level Protection Waterproof & Dustproof.
- Superior Color Reproducibility and expression to deliver High-Quality image 16BIT.
- HDR Technology delivers sharper & immersive picture quality.
- Reliable operation with Dual Power and Communication system. (Option)
- Magnesium material enables long life & less maintenance through smooth heat-dissipation.
- Cable-Free Connection minimizes apperance and defects.



HYUNDAI IT LED signage brand LEDy

With the mission to develop the advanced LED technology and bring user friendly experiences to the LED signage world. A comprehensive solution, HYUNDAI IT H Series, delievers high immersion into business with ultralightweight, any shape and size, bright and high contrast visual technology.



SPECIFICATIONS

| Model HO2.9 LED Pixel Pitch (mm) 2.976 Pixel density (dots/m²) 112,896 SMD Type Nationstar SMD1415 Module Resolution 168x84 Module Dimension (WxH/mm) 500x250 | |
|---|--|
| Module SMD Type Nationstar SMD1415 Module Resolution 168x84 | |
| SMD Type Nationstar SMD1415 Module Resolution 168x84 | |
| Module Module Resolution 168x84 | |
| Module Resolution 168x84 | |
| Module Dimension (WxH/mm) 500x250 | |
| | |
| Module quantity (WxH) 4pcs | |
| Cabinet Size 1000x500mm | |
| Maintenance Mode Front &Back | |
| Cabinet material Aluminum | |
| Brightness (Nits) 4,500 | |
| Color temperature (K) 1,000-18,500 Adjustable | |
| Viewing angle () 140(H) / 140(V) | |
| Best viewing distrance 2m | |
| Contrast Ratio 5,000:1 | |
| Refresh Frequency (Hz) 3,840 Cabinet | |
| Frequency (Hz) 50/60 | |
| Drving Mode 1/21scan | |
| Max power consumption (W/m²) 800 | |
| Avg power consumption (W/m ²) 200-300 | |
| Working Temperature (°C) -20-60 | |
| Working Humidity (RH) 10%~85% | |
| IP grade (Front/Rear) 65 / 54 | |
| Cabinet weight (kg) 12.5 | |
| Life Span (Hours) 100,000 | |

Specifications and design are subject to change without notice. See our website for detailed information.

HEAD OFFICE - HYUNDAI IT CO., LTD. 3F, 36, Sangil-ro 10-gil, Gangdong-gu, Seoul, 05288 Korea Tel. +82 70 7008 0151 E-mail: ssoh@hyundaiit.com www.hyundaiit.com

HYUNDAI IT AMERICA TECH CORP 2033 Gateway Place 5th Floor San Jose, CA 95110, USA Tel. +1 408 627 4729 email : sales@hyundaita.com www.hyundaiit.com

Full color LED display

CLASS

HO2.9 Outdoor

FEATURES

Application HDR & 16bit Gray scale

Delivering Maximum brightness, fine-tune overall picture for realistic picture Quality. HYUNDAI IT LEDy ensures long-term consistency and bring a comfortable viewing experience.

Wireless Connection Method

Cable-embedded for comfortable and clean arrangement.

Power and Data Redundancy System (Option)

Assuring the continuous operation of the screen without power failure, while the dual controllers minimize screen failure with a bi-directional signal input.


Excellent heat dissolution structure

Magnesium materials facilitate: Heat dissipation, Increase life span, Reduce maintenance.

Echo Model

Reduced Power Consumption by more than 50% compared to exisitng products Reduced electricity bills and Maximize Product life.

DIMENSIONS (Cabinet)



UPDATE: MAY. 2025

HYUNDAI IBT GMBH Carl-Zeiss-Str. 9 / 55129 Mainz, Germany Tel. +49(0) 6131 275 5350 email : info@hyundaiit.eu www.hyundaiit.eu